

IMPACT Arena

General and Technical Specification

Dimension	73.70 x 49.70 x 34.00 / 18.00 – 21.00 m. (L x W x H)
Gross Useable Space Level 1, Flat Floor Level 1, Foyer Level 3, Foyer	4,000 sq.m. (43,055.64 sq.ft.) 5,500 sq.m. (59,201.50 sq.ft.) 5,500 sq.m. (59,201.50 sq.ft.)
Floor Material	Concrete sealed material (hardened concrete)
Floor Loading Capacity Flat Floor Loading Area Foyer	2,000 kg. / sq.m. 2,000 kg. / sq.m. 750 kg. / sq.m.
Ceiling Material	Rockwool insulation and exposed steel structure
Ceiling Loading Capacity Flat Floor Stage Area Other Area	2,000 kg. / 24 sq.m. 2,000 kg. / 34 sq.m. 2,000 kg. / 40 sq.m.
Catwalk	2.00 m. in width, handrails are 1.10 m. in height on both sides
Freight Door	1 set at service area each measuring 8.00 x 4.80 m. (W x H), 26.24 x 15.74 ft. (W x H)
Entrance and Exit	L1: 16 double doors 1.90 x 2.00 m. (W x H), 6.23 x 6.56 ft. (W x H) L3: 16 double doors 1.90 x 2.00 m. (W x H), 6.23 x 6.56 ft. (W x H) L4: 24 double doors 2.00 x 2.00 m. (W x H), 6.56 x 6.56 ft. (W x H)
Restroom	19 For male, 22 for female, 2 for disabled persons and 41 private restrooms